FP-12D1UF FULL / FP-24D1UF FULL



Fiber Optic Patch Pa	
Туре	Full Patch Panel 24 Core Rack Mount(12 Port) Full Patch Panel 48 Core Rack Mount(24 Port)
Color	Black, White
Mod Jack Wiring	Full Patch Panel 24 Core Rack mount
Input Plug Type	Duplex Adaptor, SC To SC Duplex
Keystone Type	SC To SC
Material	Metal with PVC Cassette, It Has A Thick Layer Of Scratch- Resistant Blend Powder Paint, Crimp Heater
Mounting	Rack Mount
dimension	430*280*40 mm
Input Fiber Optic	It Has 4 Inputs of Reinforced By Gland To Box
Ability	Install DX Duplex Adapter











FP-12D1UR FULL / FP-24D1UR FULL



Fiber Optic Patch	Panel
Туре	Full Patch Panel 24 Core Rail Mount (12 Port) Full Patch Panel 48 Core Rail Mount (24 Port)
Color	Black, White
Mod Jack Wiring	Full Patch Panel 48 Core Rail Mount
Input Plug Type	Duplex Adaptor, SC To SC Duplex
Keystone Type	SC To SC
Material	Metal with PVC Cassette, It Has A Thick Layer Of Scratch-Resistant Blend Powder Paint, Crimp Heater
Mounting	Rail Mount
dimension	430*280*40 mm
Input Fiber Optic	It Has 4 Inputs Of Reinforced By Gland To
Ability	Install DX Duplex Adapter

FP-06D1UW FULL



Type Patch Panel 12 Core Wall mount (6 Port) Color BLACK, White Mod Jack Wiring Full Patch Panel 12 Core Wall mount Input Plug Type Duplex Adaptor, SC To SC Duplex Keystone Type SC To SC	
Mod Jack Wiring Full Patch Panel 12 Core Wall mount Input Plug Type Duplex Adaptor, SC To SC Duplex	
Input Plug Type Duplex Adaptor, SC To SC Duplex	
Keystone Type SC To SC	
,	
Metal with PVC Cassette, It Has A Thick Li Scratch-Resistant Blend Powder Paint, Crimp Hea	yer Of ter
Mounting Wall Mount	
dimension 115*290*45 mm	
Input Fiber Optic It Has 2 Inputs of Reinforced By Gland To Box	
Ability Install DX Dublex Adapter	

FP-06D1UD FULL



Fiber Optic Patch	Panel
Туре	Full Patch Panel 12 Core Din rail (6 Port)
Color	BLACK, White
Mod Jack Wiring	Full Patch Panel 12 Core Din rail
Input Plug Type	Duplex Adaptor, SC To SC Duplex
Keystone Type	SC To SC
Material	Metal with PVC Cassette, It Has A Thick Layer Of Scratch-Resistant Blend Powder Paint, Crimp Heater
Mounting	Din rail
dimension	193*167*45 mm
Input Fiber Optic	It Has 2 Inputs of Reinforced By Gland To Box
Ability	Install DX Dublex Adapter