



2 years  
Silver  
Guarantee

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

### سایر برتری‌ها:

- بدنه ضد آب و گرد و غبار با درجه IP67
- سرور انتقال تصویر در ایران
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند

Camera	
Image Sensor	5MP Progressive scan Cmos Sensor (1/2.7")
CPU	Single-Core ARM Cortex-A7@750MHz
Lens	3.6 mm Fixed Lens @F1.6
Resolution	2592*1944 (5MP)
Available IR Range	30~40 M Smart IR LED (Philips) Technology
D/N Filter	IR cut filter with auto switch
Min Illumination	Color: 0.01 Lux(AGC on) - B/W: 0.0 Lux(IR on)
Angle of View	H-FOV: 85°, V-FOV: 44°, D-FOV: 89°
StarLight View	N/A
Picture Adjust	
Picture Function	DWDR, BLC, HLC, Defog, ROI, Rotate
Shutter Speed	Manual (1/3 ~ 1/10.000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265) Smart Event Codec
Audio Compression	N/A
Frame Rate(60Hz)	20fps@ 5MP, 25fps@ 4MP, 30fps@ 2MP
Transmission Stream	Dual Stream (Video Bit Rate:11 Kbps~10 Mbps)
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, UPnP-TM, P2P, Bonjour, IPV6 (NO FTP)
Compatibility	Onvif Ver2.6, Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Smart Device	IOS, Android Phone & Tablet

Function	
Recording	NVR, CMS, VMS
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	All Intelligent Function
Event Action	Email, PTZ, Snapshot, Recording, Buzzer, Pop up, Show Message
Event	Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	1 RJ45 (10M / 100M) Ethernet Port
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC In
Control	N/A
Memory Slot	N/A
General	
IP Rating	IP67
Power Supply	DC12V ± 10%
POE Supply	IEEE802.3af - Max 6.5 Watt
Web Language	English, Persian
Dimension	152*65*74 mm
Weight	365 g
Operation Humidity	Humidity 95% or less (non-condensing)
Operation Temp	-45°C ~ +75°C
Guarantee	
Product Guarantee	2 Years Silver Guarantee
MTBF	150K hrs min- MIL-HDBK-217F (25°)
Certificates	EN, CN, FCC, CFR