


*نکته: این محصول بدون پایه ارائه می گردد.



2021-Q2

5 years Gold Guarantee

- پنج سال گارانتی طلایی بدون قید و شرط کی دی تی
- شش سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 256Gb
- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265+
- بدنه ضد ضربه با استاندارد IK10
- پشتیبانی از ONVIF ورژن 2.4
- قابلیت دید در شب هوشمند
- قابلیت WDR, BLC, HLC, Defog

قابلیت‌های هوشمند:

- عبور از خط
- تشخیص حرکت
- ورود به منطقه

Camera	
Image Sensor	2MP Starlight (Sony-Japan) Cmos Sensor (1/2.9")
CPU	Dual-Core ARM Cortex-A7@900MHz
Lens	20X Optical Lens (5.4~108mm)
Resolution	1920x 1080 (2MP)
Available IR Range	120~140M IR SMD (Osram-Germany) Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: 0.01 Lux(AGC on) - B/W: 0.0 Lux(IR on)
Angle of View	H-FOV: 3°~53°, V-FOV: 2°~41°, D-FOV: 4°~64°
StarLight View	Yes-Color
Picture Adjust	
Picture Function	120db WDR, DWDR, BLC, HLC, Defog, ROI
Shutter Speed	Manual (1/3 ~ 1/100.000), Auto
Image Parameter Control	Off, On, Timing (Adjust 0 ~ 255)
D/N Control	Timing, Auto, Color on, Color off
Image Parameter	Saturation, Brightness, Contrast, Sharpness, Hue
Video / Audio	
Video Compression	H.264+(Ultra H.264), H.265+ (Ultra H.265)
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@1080P(WDR on)
Transmission Stream	Triple Stream (Code Rate: 128kb-16mb)
Network	
Protocols	HTTPs, HTTP, TCP/IP V4-V6, ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, UPNP, SIP, NAT
Compatibility	Onvif Ver2.4, Profile S, CGI, SDK, API
Max Users	10 Users
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer
Recording Software	Unlimited KDT CMS/VMS 128CH Per Monitor

Function	
Recording	FTP, NVR, CMS, NAS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	Motion Detection, Alarm In
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out, Buzzer, Pop up, Show Message
Intelligent Function	3 Smart Function Line Crossing, Entering The Area, Motion Detection
Interface	
Network	RJ45(10/100Mbps)
Audio	Audio Out, Audio In
Alarm	Alarm Out, Alarm In
CVBS	N/A
Power	PoE LAN, DC In
Control	RS485
Memory Slot	Yes - Micro SD (128Gb Max)
General	
IP Rating	IP67, IK10
Lens Cover	Nano Glass
Power Supply	DC12V ± 25%
POE Supply	IEEE802.3af-Max 13W(0-270A)
Web Language	English, Persian
Dimension	121*100*227 mm
Weight	1.2 Kg
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-45°C ~ +75°C
Guarantee	
Product Guarantee	5 Years Gold Guarantee
MTBF	100K hrs min- MIL-HDBK-217F (25°)