



1402-S1

**2 years
Silver
Guarantee**

- دو سال گارانتی نقره‌ای بدون قید و شرط کی دی تی
- سه سال ضمانت پایداری کیفیت تصویر

سایر برتری‌ها:

- پشتیبانی از میکرو SD با ظرفیت 128GB
- بدنه ضد آب و گرد و غبار با درجه IP67
- پشتیبانی از H.264+ / H.265+
- پشتیبانی از ONVIF ورژن 2.6
- قابلیت دید در شب هوشمند
- قابلیت WDR، BLC، HLC، Defog و ROI تا ۸ ناحیه

Camera	
Image Sensor	4MP (Sony-Japan) Progressive scan Cmos Sensor (1/2.8")
Case Size	6"
CPU	Dual Core ARM Cortex-A7@ 900 MHz
Lens	33X Optical Lens (5.3~175 mm) (F-Stop F1.6~F5.8)
Resolution	2592*1520 (4MP)
Available IR Range	200~210 m Smart IR SMD Technology
D/N Filter	IR Cut Filter Switch (ICR)
Min Illumination	Color: 0.002 Lux(AGC on) - B/W: 0.0 Lux(IR on)
PTZ	Pan Range: 0°~360° Endless - Pan Speed: 0°~170°/S Tilt Range: 0°~95° - Tilt Speed: 0°~80°/S Number of Preset: 255 - Patrol: 8 - Pattern: 8 - Park Action: NO
Night Vision	Color /IR
Picture Adjust	
Picture Function	120 db WDR/DWDR, 2D/3D DNR, BLC, HLC, ROI, Defog
Shutter Speed	Manual (1/25 ~ 1/100.000), Auto
Image Control	Off, On, Timing (Adjust 0 ~ 100)
D/N Control	Timing, Auto, Color on, Color off
Image Setting	Brightness, Contrast, Saturation, Sharpness, Chroma
Video / Audio	
Video Compression	H.264, H.264+, H.265, H.265+
Audio Compression	G.711A, G.711U
Frame Rate(60Hz)	30fps@4MP, 30fps@ 1080P
Transmission Stream	Triple Stream (Code Rate: 128kbps-16mbps)
Network	
Protocols	HTTPs, HTTP, TCP/IP V4-V6, ICMP, RTSP, UDP, NTP, DHCP, DDNS, FTP, SNMP-V1-V2-V3, Multi Cast
Compatibility	Onvif Ver2.4, Profile S, CGI, SDK, API
Streaming Method	Unicast, Multicast
Web Viewer	Internet Explorer

Function	
Recording	FTP, NVR, CMS,VMS, SD Card
Record Type	Manual, Motion Detection, Smart Detection, Schedule
Alarm Triggers	N/A
Event Action	Email, PTZ, Snapshot, Recording, Alarm Out
Event	Motion Detection, Video Shelter
Intelligent Function	N/A
Interface	
Network	RJ45(10/100mbps)
Audio	N/A
Alarm	N/A
CVBS	N/A
Power	PoE LAN, DC/AC In
Reset Button	N/A
Memory Slot	Yes - Micro SD/SDHC/SDXC Slot (128 Gb Max)
General	
IP Rating	IP67, 3KV Surge Protection
Power Supply	AC12 V ± 25% (4A Max)
POE Supply	IEEE802.3at-af-Max 25 Watt
Web Language	English, Persian
Dimension	374*287*276 mm
Weight	5 kg
Operation Humidity	Max Up to 95%RH(Non Condensing)
Operation Temp	-40°C ~ +70°C
Guarantee	
Product Warranty	2 Years Silver Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)