

NC-Cuprum 6SFTPO



Conductor	
Size	23 AWG
Design Type	Spacer / Copper Wires / 1 Jacket/ Shield/Foil
Diameter (mm)	0.5 ± 0.55
Insulation	
Type	SFTP Outdoor
Cable Diameter	Nom. 5.5±0.5 mm
Jacket Thickness	Nominal Thickness = 0.59 mm
Shielding	Aluminium / Polyester Foil
Physical	
1. Cold Bend Test	-30 ± 2°C X 4hrs no crack
2. Dielectric strength	AC 1.7KV for 2s
Jacket	
Min Bending Radius	50 mm
Installation Temperature	-10°C to +65°C
Jacket	
Type	Polyethylene
Overall Diameter	8.3 ± 0.3 mm



1403-S3

NC-Cuprum 6SFTPI-LSZH



Conductor	
Size	23 AWG
Design Type	Spacer / Copper Wires / 1 Jacket/ Shield/Foil
Diameter (mm)	0.5 ± 0.55
Insulation	
Type	SFTP Indoor
Cable Diameter	Nom. 5.5±0.5 mm
Jacket Thickness	Nominal Thickness = 0.56 mm
Shielding	Aluminium / Polyester Foil
Physical	
1. Cold Bend Test	-30 ± 2°C X 4hrs no crack
2. Dielectric strength	AC 1.7KV for 2s
Jacket	
Min Bending Radius	50 mm
Installation Temperature	-20°C to +65°C
Jacket	
Type	Low Smoke Zero Halogen(LSZH)
Overall Diameter	8.1 ± 0.3 mm